



Piston Spex Sheet

Powered By EngineWorx

Date: 3/25/2022

Piston Part # BTRP416125FT5

[2-Cycle Traveler Click Here](#)

Piston Description:

[4-Cycle Traveler Click here](#)

Piston Specifications

Bore (IN):	4.0650
Bore (MM):	103.25100
Piston Diameter (IN)	4.0610
Piston Diameter (MM)	103.1494
Dome Volume (CC):	-1.8
Material:	Not Specified
Piston Style:	Dished
Compression Height (IN):	1.1150
Target Weight (G):	490.000
Dome Height (IN):	0.0000
Dome Thickness (IN):	Not Specified
Piston Clearance (IN):	0.0040
Piston Clearance (MM):	0.1016
Pin Offset	0.0000
Pin Offset Direction	Not Specified
Forging	F6473X

Skirt Mill

	<i>Intake</i>	<i>Exhaust</i>
Over All Length From TE	2.1785	2.1785

Valve Pocket Specifications

	<i>Intake</i>	<i>Exhaust</i>
Diameter (IN):	2.3000	1.7500
Angle (DEG):	14.00	14.00
Depth to T/E	-0.1250	-0.1500

2 Cycle

	Top	Second
Pin Angle	Not Specified	Not Specified
Distance to C/L	Not Specified	Not Specified
Direction	Not Specified	Not Specified

Coating Specifications

	Coating Type	Coating Thickness
Coating 1	SC	0.0005
Coating 2	Not Specified	Not Specified
Coating 3	Not Specified	Not Specified

Ring Specifications

Ring Set Part #	Not Specified
Bore (IN):	Not Specified
Bore (MM):	Not Specified
Style:	Not Specified

Wrist Pin Specifications

Pin Part #:	S643
Diameter (IN):	0.92700
Diameter (MM):	23.54580
Length (IN):	2.25000
Length (MM):	57.15000
Wall Thickness (IN):	0.14850
Wall Thickness (MM):	3.77000
Material:	5115
Coating:	Unchromed
Weight (G):	104.50000

Retainer Clip Specifications

Retainer Clip Part #	CS24
Diameter (IN):	0.9270
Diameter (MM):	0.0000
Type:	Spiral
Thickness (IN):	0.0720
Material:	SAE 1070-1090

Oil Rail Support Specifications

Oil Rail Support Part #	GLS26
Minimum Bore (IN):	4.03800
Maximum Bore (IN):	4.07500
Radial Wall Thickness (IN):	0.16000

Stamping Specifications

Workorder/Date Code?	Y
Entire Part Number?:	Y
Spec Number?:	N
Directional?:	N
Directional Instructions:	Not Specified

