



BTR GEN V 220

GEN V LT APPLICATIONS

INTAKE DURATION @ .050"	220°	LSA	113°
EXHAUST DURATION @ .050"	23X°	INSTALL DOT-DOT	
NET LIFT INTAKE	0.644"	FUEL LOBE	32%
NET LIFT EXHAUST	0.644"	*ACTUAL SPECS MAY VARY	

BTR GEN V 220

SEE VVT TABLE ON REVERSE SIDE

BTR LT1 220

RPM	4000	4200	4400	4600	4800	5000	5200	5400	5600	5800	6000	6200	6400	6600	6800	7000
DEG	0.0	0.0	0.0	2.0	3.0	0.0	0.0	0.0	2.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0

BTR L86 220

RPM	4000	4200	4400	4600	4800	5000	5200	5400	5600	5800	6000	6200	6400	6600	6800	7000
DEG	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0

BTR L83 220

RPM	4000	4200	4400	4600	4800	5000	5200	5400	5600	5800	6000	6200	6400	6600	6800	7000
DEG	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	2.0	2.5	3.0	4.0	4.0	4.0	4.0